



# Compression Fittings

RECOMMENDED FOR USE WITH *JetTubes*<sup>™</sup> (see page 18)

■ Available in NPT and BSPT pipe threads

**DIMENSIONS IN INCHES (except as noted)**

MALE CONNECTOR (includes nut and sleeve)							
Part No.	Tube Size	Thread "E"	Straight Thread (Nut End)	"C" Hex	L	Pkg Qty	Configuration
CF15510	3/16	1/16 NPT/BSPT	3/8 - 24 UN	7/16	1.08	5	
CF15010		1/8 NPT		7/16	1.08	5	
CF15210		1/8 BSPT		7/16	1.08	5	
CF15030		1/4 NPT		9/16	1.27	5	
CF15230		1/4 BSPT		9/16	1.27	5	
CF15530		M8x1.0		7/16	1.10	5	
CF15535		M8x1.25		7/16	1.10	5	
CF15538		M10x1.0		7/16	1.13	5	
CF15540		M10x1.25		7/16	1.13	5	
CF15545		M10x1.5		7/16	1.13	5	
CF15020	1/4	1/8 NPT	7/16 - 24 UN	7/16	1.10	5	
CF15220		1/8 BSPT		7/16	1.10	5	
CF15040		1/4 NPT		9/16	1.30	5	
CF15240		1/4 BSPT		9/16	1.30	5	
CF15550		M12x1.75		1/2	1.20	5	
CF15025	5/16	1/8 NPT	1/2 - 24 UN	1/2	1.15	5	
CF15225		1/8 BSPT		1/2	1.15	5	
CF15050		1/4 NPT		9/16	1.33	5	
CF15250		1/4 BSPT		9/16	1.33	5	
CF15060	3/8	1/4 NPT	9/16 - 24 UN	9/16	1.42	5	
CF15260		1/4 BSPT		9/16	1.42	5	
CF15070		3/8 NPT		11/16	1.44	5	
CF15270		3/8 BSPT		11/16	1.44	5	

MALE ELBOW (includes nut and sleeve)							
Part No.	Tube Size	Thread "E"	Straight Thread (Nut End)	L	N	Pkg Qty	Configuration
CF15110	3/16	1/8 NPT	3/8 - 24 UN	.84	.69	5	
CF15310		1/8 BSPT		.84	.69	5	
CF15130		1/4 NPT		.86	.93	5	
CF15330		1/4 BSPT		.86	.93	5	
CF15120	1/4	1/8 NPT	7/16 - 24 UN	.86	.74	5	
CF15320		1/8 BSPT		.86	.74	5	
CF15140		1/4 NPT		.86	.94	5	
CF15340		1/4 BSPT		.86	.94	5	
CF15125	5/16	1/8 NPT	1/2 - 24 UN	.88	.74	5	
CF15325		1/8 BSPT		.88	.74	5	
CF15150		1/4 NPT		.95	.93	5	
CF15350		1/4 BSPT		.95	.93	5	
CF15160	3/8	1/4 NPT	9/16 - 24 UN	1.03	.93	5	
CF15360		1/4 BSPT		1.03	.93	5	
CF15170		3/8 NPT		1.03	1.00	5	
CF15370		3/8 BSPT		1.03	1.00	5	

NUT					
Part No.	Tube Size	Internal Thread	"C" Hex	Pkg Qty	Configuration
CF15410	3/16	3/8 - 24 UN	7/16	25	
CF15420	1/4	7/16 - 24 UN	1/2	25	
CF15422	5/16	1/2 - 24 UN	9/16	25	
CF15424	3/8	9/16 - 24 UN	5/8	25	

SLEEVE			
Part No.	Tube Size	Pkg Qty	Configuration
CF15430	3/16	25	
CF15440	1/4	25	
CF15450	5/16	25	
CF15460	3/8	25	

Material: Brass    Maximum Pressure: 500 PSI (33 bar)    Maximum Operating Temperature: 300°F (150°C)

**Ordering Information**

Determine if your machine employs NPT or BSPT ports. Order connectors and elbows to suit. Order spare nuts and sleeves to enable easy swapping of *JetTubes* without changing connectors.